



RATED POWER
10 kVA 12 kVA 15 kVA

Shore Power Converter AC/AC Single Phase

SINGLE CABINET



Advantages for the vessel and owner



- **Protection of the vessel's electrical system** thanks to the galvanic isolation provided by the native isolation transformer on all converters used on this line
- Converters **can operate in automatic mode with any voltage and frequency** provided by the dockside service, anywhere in the world
- **Shore-side voltage fluctuations do not affect onboard power quality.** The converter continues to deliver stable voltage, constant frequency and clean current regardless of what occurs at the dockside
- **High performance** thanks to the state-of-the-art technologies available on the market, lower electricity costs
- Thanks to the native double conversion system, the converter is able to **regenerate any excess power delivering it to the grid**
- Each converter on this line **consists of modules that are easily assembled on site** as and when needed; this provides for more straightforward logistics and swifter installation
- **No calibration is required** over time and routine maintenance is reduced to a minimum



ON Board

The information and specifications provided are indicative only and do not constitute a contractual commitment. The manufacturer reserves the right to make modifications without prior notice.



SPC010-S1 **10KVA**
SPC012-S1 **12KVA**
SPC015-S1 **15KVA**

Shore Power Converter AC/AC Single Phase

SINGLE CABINET



Main technical specifications



- Use of **high efficiency** isolation transformers
- Use of **silicon carbide modules to contain volume and temperatures**, increasing overall efficiency
- **Protective coating of all printed circuit boards installed**, to guarantee longer service life and higher quality operation over time
- **Monitoring and logging** of operating and cooling system **temperatures** for precise component management
- **Modular design** for faster and easier maintenance
- **Touchscreen monitor** for user-friendly operations
- **Standard emergency push-button**, input and output contactor installed on each machine to boost safety levels
- **Aluminium and Stainless Steel** structure, painted to prevent corrosion over time
- **User-enabled auto-restart.** This allows the converter to automatically power up again after a dockside blackout

Optional accessories



- Second remote touchscreen panel
- Communication with the vessel's PMS via Modbus RTU (RS485)
- Communication with the vessel's PMS via Modbus TCP/IP (Ethernet)
- Remote support (via internet network provided by the vessel)
- Multi-language control display
- Seamless transfer between converter and generator
- Up to 4 clean contacts to interface with the vessel's system



ON Board

The information and specifications provided are indicative only and do not constitute a contractual commitment. The manufacturer reserves the right to make modifications without prior notice.



SPC010-S1 **10KVA**
SPC012-S1 **12KVA**
SPC015-S1 **15KVA**

Shore Power Converter AC/AC Single Phase

SINGLE CABINET

TECHNICAL DATA

Input SPC010-S1 SPC012-S1 SPC015-S1

Power Form	Single Phase		
Input connection	Single Cord		
Voltage	180-260 or 190/520* VAC (to be specified)		
Frequency	45/65 Hz		
Max current	Max 48 A	Max 58 A	Max 73 A
Power factor	≥ 0.99 at rated load		
Inrush current	<50% of nominal current		
THDi	<3% at rated load		
Phase sequence	Any		
Protections	Overvoltage, Overcurrent, Shortcircuit, Loss of Phase, Transients		

* 190-260 and 350-520 VAC

Output @ p.f. 1

Power form	Single Phase
Output connection	Single Phase/Split Phase
Voltage	110/220 - 115/230 - 120/240 Vac 220 - 230 - 240 Vac
Frequency	50 or 60 Hz
THDv (linear load)	<1.5%
Voltage tolerance	0.5%
Frequency tolerance	0.1%
Overload 125%	10 min
Overload 150%	3 min
Overload 200%	4 sec

Environment

Working temperature	0-50 °C**
Humidity	0-95% non condensing
IP grade	IP 20***
Cooling	Forced Air cooled

** derating over 40°C *** other IP standards available on request

Dimensions and Weight

Width	37.0 cm - 14.6 in
Depth	65.0 cm - 25.6 in
Height	60.5 cm - 23.8 in
Weight	155 kg****

**** weight may vary depending on power rating and configuration

Clearances

Sides	0.0 cm - 0.0 in
Over	12.0 cm - 4.7 in *****
Back	10.0 cm - 3.9 in
Front	45.0 cm - 17.7 in

***** (for maintenance)



ON Board

The information and specifications provided are indicative only and do not constitute a contractual commitment. The manufacturer reserves the right to make modifications without prior notice.



SPC010-S1 10KVA
SPC012-S1 12KVA
SPC015-S1 15KVA


Shore Power Converter AC/AC Single Phase

SINGLE CABINET

TECHNICAL DRAWINGS




EMERGENCY BUTTON
TOUCHSCREEN
SWITCH ON-OFF



FRONT VIEW

←
AIR FLOW



VIEW SIDE

- 1 Control module - detachable
- 2 Power module - detachable
- 3 Transformer module - detachable



ON Board

*This drawing is the property of A.S. Marine Power Solutions.
Unauthorized reproduction, disclosure, or use is strictly prohibited.*

The information and specifications provided are indicative only and do not constitute a contractual commitment. The manufacturer reserves the right to make modifications without prior notice.